



TFA s.r.o.
Procházková 430
Kostelec nad Orlicí 517 41
DIČ: CZ02543419
CZECH REPUBLIC

tvoda@tfa.cz
www.tfa.cz



Phone: +420 733 304 659
+420 494 323 575
800 400 246

CZ INNOVATION FOR WINTER

Waxpo Digital

ONE MACHINE CONTAINS THREE TECHNOLOGIES

for waxing, brushing and polishing of ski and snowboard skids in the width of up to 350 mm.

PRODUCT ADVANTAGES

STANDARD PRODUCT SPECIFICATION

Digital setting and control of the desired wax temperature with progressive or tuning temperature heating start including a digital indicator for the selected and real temperature

Indicator of wax temperature in degrees Celsius or Fahrenheit with measuring range from one tenth of the degree

A temperature sensor located directly in the wax bath

Digital control of the waxing roller start-up

At the purchase the selection of the heating capacity and other accessories such as stable legs, a side rack for freshly waxed skis, LED lights for the working area

An integrated stainless steel hopper for wax granules, a tilting stainless-steel heat shield of the waxing roller and a drawer for brushed-off waste, a stainless-steel height-adjustable control panel

A waxing tank made of Al alloy, the tank can be replaced with another one with a different type of wax

1600 W heating bodies are outside the waxing tank and they guarantee gentle heating of wax without side effects

Simple, fast and well-arranged operating and maintenance functions

A quiet maintenance-free drive of the brushing and polishing roller by means of tooth-belts

New brush design using modern PA-6 materials



EUROPEAN UNION
European Regional Development Fund
Operational Programme Entrepri-
se and Innovations for Competitiveness

OPTIONAL ACCESSORIES

Heating bodies with the power of 1800 W or 2100 W

4x stabilization legs with setting screws or travel wheels

Side rack for a freshly waxed ski or snowboard

LED lights for the working area

A spare wax tank with a temperature sensor

A side shelf for the area at the machine legs



TECHNICAL DATA		
WAXPO DIGITAL		
Weight	kg	108
Total power	kW	2,5 /to specification 2,7 or 3/
Power supply	V	3 x 400 V – AC, 50 Hz
Protection	A	16
Width of waxing roller	mm	350
Revolutions of waxing roller	rev/min	90
Width of brushes	mm	350
Revolutions of brushes	rev/min	1000

